

DATE

20210317



YNE SERIES

Model YNE138RB Inlet air temp 30°C
 Atmos humidity 80%R. H. Discharge air temp 85°C
 Inlet air pressure 1atm Inlet oil temp 60°C

Direct driven

	Discharge MPa	0.7	0.8	1.0	1.25	1.5
rpm						
1780	Shaft power kW	22.7	24.8	28.1	32.7	38.7
	m³/min	3.84	3.81	3.75	3.60	3.42
	Oil consumption kW	18.2	19.9	22.5	26.1	31.0
	Oil injection L/min	29.7	33.1	38.5	46.0	56.0
2200	Shaft power kW	27.9	30.5	34.6	40.2	47.6
	m³/min	4.72	4.68	4.61	4.43	4.21
	Oil consumption kW	22.3	24.4	27.7	32.2	38.1
	Oil injection L/min	36.5	40.8	47.4	56.6	68.8
2975	Shaft power kW	37.5	41.0	46.5	54.0	64.0
	m³/min	6.50	6.45	6.35	6.10	5.8
	Oil consumption kW	30.0	32.8	37.2	43.2	51.2
	Oil injection L/min	48.8	54.5	63.4	75.8	92.2
3570	Shaft power kW	45.2	49.4	56.1	65.1	77.2
	m³/min	7.76	7.70	7.58	7.28	6.93
	Oil consumption kW	36.2	39.6	44.9	52.1	61.7
	Oil injection L/min	59.0	65.8	76.6	91.5	111.4

According to International organization for standardization (ISO) ISO 1217-2009 positive displacement compressor acceptance tests.

Импортер: ООО «Рутектор»

Адрес: 109456, Россия, Москва,

1-й Вешняковский проезд, д.1 (строение 11)

+7 495 660-0069 info@rutector.ru rutector.ru