



YNE系列主机参数

主机型号	YNE163RA	进气温度	30℃
大气湿度	80%R. H.	排气温度	85℃
进气压力	1atm	进油温度	60℃

皮联传动							
排压MPa 轴功率kW		0. 7	0. 8	1	1. 25	1. 5	油耗能kW
61	转速rpm	3150	2950	2600	2200	1850	48. 8
	气量m³ /min	9. 9	9. 25	8	6. 6	5. 5	
	喷油量L/min	80. 5	81. 6	83. 7	86. 1	88. 0	
82. 5	转速rpm	4250	3900	3500	3000	2550	66. 0
	气量m³ /min	13. 2	12. 3	10. 7	9. 1	7. 4	
	喷油量L/min	109. 2	110. 7	113. 5	116. 2	119. 0	
直联传动							
排压MPa 转速rpm		0. 7	0. 8	1. 0	1. 25	1. 5	1. 7
1780	轴功率kW	35. 2	37. 5	41. 5	48. 0	56. 0	66. 0
	气量m³ /min	5. 50	5. 40	5. 35	5. 20	5. 10	4. 90
	油耗能kW	28. 2	30. 0	33. 2	38. 4	44. 8	52. 8
	喷油量L/min	46. 8	50. 7	57. 1	67. 7	80. 7	96. 9
2200	轴功率kW	43. 0	46. 0	51. 0	59. 0	69. 0	79. 2
	气量m³ /min	6. 90	6. 80	6. 70	6. 52	6. 30	6. 08
	油耗能kW	34. 4	36. 8	40. 8	47. 2	55. 2	63. 3
	喷油量L/min	56. 9	61. 8	70. 0	83. 0	99. 4	116. 0
2975	轴功率kW	57. 0	60. 5	67. 5	78. 0	91. 0	107. 0
	气量m³ /min	9. 35	9. 25	9. 14	8. 90	8. 60	8. 30
	油耗能kW	45. 6	48. 4	54. 0	62. 4	72. 8	85. 6
	喷油量L/min	75. 1	80. 8	92. 2	109. 3	130. 5	156. 6
3570	轴功率kW	69. 8	74. 1	82. 6	95. 5	111. 4	131. 0
	气量m³ /min	11. 16	11. 04	10. 91	10. 63	10. 27	9. 91
	油耗能kW	55. 8	59. 2	66. 1	76. 4	89. 1	104. 8
	喷油量L/min	92. 4	99. 4	113. 3	134. 3	160. 2	192. 1